

Gaine thermorétractable à paroi fine

Heatshrinkable thin wall tubing

Polyoléfine flexible enduite d'adhésif thermofusible

Flexible polyolefin, dual wall adhesive lined

Grade industriel & militaire - Industrial & military purpose

PLDW 104

Spécifications industrielles internationales - International industrial specifications:

SAE-AMS-DTL-23053/4

UL 224 125°C VW1 600V, RoHS

Auto-extinguible - Self-extinguishible

Rétreint 4/1 - Shrink ratio 4/1

Température d'utilisation - Operating temperature : -45°C / +125°C

Couleur standard : Noir

Standard colors : Black

Couleurs non standard : Sur demande

Non standard colors : Available on request



Références References	Diamètre - Diameter Expanse mini - Recouv. maxi Mini expanded - Maxi recovered mm	Épaisseur paroi nominale Nominal wall thickness mm	Conditionnement - Packaging Bobine Spool m	Barres Lengths 1,22 m
PLDW 104 4/1	4,0 / 1,0	1,00	150	50
PLDW 104 8/2	8,0 / 2,0	1,10	75	25
PLDW 104 12/3	12,0 / 3,0	1,40	60	25
PLDW 104 16/4	16,0 / 4,0	1,60	50	25
PLDW 104 24/6	24,0 / 6,0	2,15	50	15
PLDW 104 32/8	32,0 / 8,0	2,40	25	10
PLDW 104 52/13	52,0 / 13,0	2,40	50	15

Découpe de manchons à la demande - Cutting available on request